

2

Rust Remover MoS2

- Quickly dissolves thick rust formations
- Very good creep behavior
- Dissolves gummed and stiff joints and door hinges
- Protects against wearout, corrosion
- Prevents squeaking and creaking sounds

Application Area

- Loosening rusted screw connections and resin deposits

Characteristics

- Temperature-resistant -40 °C to +300 °C.
- Pressure and wear resistance value (VKA): 900N.
- Free of resin, silicone and acid.

Processing Information

- MoS2 rust remover 5L application through using: Pump Nozzle Dissolving [Art.no.81 869].
- Spray at a distance of 15-20 cm and let evaporate.
- After use, briefly hold the container upside down in order to clean the spray nozzle and the valve.
- Remove dirt.

Technical Data

Color	Brown / black
VKA Value	900 N
Temperature resistance	-39 °C - 300 °C

Title	Container	Content	PU Amount	Article No.
Rust Remover MOS2	Canister	5 l	1	213963
RUST REMOV MOS2 SPRAY 400ML	Spray can	400 ml	1/30	207445

AGR: 04.010 / 04.011

Accessories Available	PU Piece	Article No.
Capillary Tube 100 mm	1	029106
Dispensing Tap for 5 l	1	413720
Spray Heading with Spray Pipe	1	134245

